Printing date 03.11.2022 Version number 4 Revision: 03.11.2022 SECTION 1: Identification of the substance/mixture and of the company/undertaking · 1.1 Product identifier · Trade name: Flüssigkeit für SHERADON · Article number: 508010 · 1.2 Relevant identified uses of the substance or mixture and uses advised against: No further relevant information available. · Application of the substance / the mixture: Manufacture of dental products. · 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Manufacturer: retec® Kunststofftechnik GmbH Industriestrasse 2 D-61191 Rosbach v.d.H +49 (0) 6007 91570 info@retec-dent.de www.retec-dent.de Contact person: Dr. Manfred Steinbach Supplier: SHERA Material Technology GmbH & Co. KG Espholstrasse 53 D-49448 Lemfoerde sdb@shera.de + 49 (0) 5443 9933-0 · Further information obtainable from: Department of product security. · 1.4 Emergency telephone number: Giftinformationszentrum-Nord +49 (0) 551-19240 (Information in german or english) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture · Classification according to Regulation (EC) No 1272/2008: Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

· 2.2 Label elements

• Labelling according to Regulation (EC) No 1272/2008: The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms:



· Signal word: Danger

 Hazard-determining components of labelling: methyl methacrylate

tetramethylene dimethacrylate • Hazard statements:

H225 Highly flammable liquid and vapour. H315 Causes skin irritation.

(Contd. on page 2)

Printing date 03.11.2022 Version number 4 Revision: 03.11.2022 Trade name: Flüssigkeit für SHERADON (Contd. of page 1) H317 May cause an allergic skin reaction. H335 May cause respiratory irritation. · Precautionary statements: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid breathing dust / fume / gas / mist / vapours / spray. P261 Use only outdoors or in a well-ventilated area. P271 P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P302+P352 IF ON SKIN: Wash with plenty of water. P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse. P370+P378 In case of fire: Use CO2, powder or water spray to extinguish. P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents / container in accordance with local / regional / national / international regulations. · 2.3 Other hazards · Results of PBT and vPvB assessment: · PBT: Not applicable. · vPvB: Not applicable. SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture based on methyl methacrylate.

· Dangerous components:

Dangerous components.		
CAS: 80-62-6	methyl methacrylate	
EINECS: 201-297-1 Index number: 607-035-00-6 Reg.nr.: 01-2119452498-28	Flam. Liq. 2, H225; Skin Irrit. 2, H315; Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 2082-81-7 EINECS: 218-218-1 Index number: 607-134-00-4 Reg.nr.: 01-2119967415-30	tetramethylene dimethacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	5-<10%

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

- Get medical advice if you feel unwell.
- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:

Clean with water and soap. If possible, also wash with polyethylene glycol 400.

- Seek medical treatment.
- \cdot After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:
- If symptoms persist consult doctor.
- Rinse out mouth and then drink plenty of water.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

GB

Printing date 03.11.2022

Version number 4

Revision: 03.11.2022

(Contd. of page 2)

Trade name: Flüssigkeit für SHERADON

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet.
- · 5.2 Special hazards arising from the substance or mixture Can form explosive gas-air mixtures.
- · 5.3 Advice for firefighters
- · Protective equipment:
- Wear fully protective suit.
- Wear self-contained respiratory protective device.
- · Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Keep away from ignition sources.
 Ensure adequate ventilation.
 Do not breathe vapour or spray.
 Avoid contact with skin and eyes.
 Wear respiratory protection.
 6.2 Environmental precautions Do not allow to enter sewers / surface or ground water.
- \cdot 6.3 Methods and material for containment and cleaning up
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

6.4 Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation / exhaustion at the workplace. Do not breathe vapours. Do not breathe spray.
 Information about fire - and explosion protection: Fumes can combine with air to form an explosive mixture. Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles: Keep container tightly closed.
 Keep container in a well ventilated, cool and dry place
- Keep container in a well-ventilated, cool and dry place.
- Information about storage in one common storage facility: Do not store together with:

(Contd. on page 4)

GB

Version number 4

Revision: 03.11.2022

(Contd. of page 3)

Trade name: Flüssigkeit für SHERADON

Printing date 03.11.2022

Oxidising agent. Pyrophorics or self-heating hazardous material.

- · Further information about storage conditions: Keep away from sources of ignition and heat.
- · Storage class: No information available.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

•••••••••••••••	
· Ingredients with lin	nit values that require monitoring at the workplace:
80-62-6 methyl met	hacrylate
WEL (Great Britain)	Short-term value: 416 mg/m³, 100 ppm Long-term value: 208 mg/m³, 50 ppm
AGW (Germany)	Long-term value: 210 mg/m³, 50 ppm 2(I);DFG, EU, Y
IOELV (EU)	Short-term value: 100 ppm Long-term value: 50 ppm
2082-81-7 tetramet	hylene dimethacrylate
MAK (Germany)	cf. Section IV
· DNELs:	
80-62-6 methyl met	hacrylate

Dermal DNEL Worker - Long Term - Systemic effects 17 mg/kg /KG/d (workers)

Inhalative DNEL Worker - Long Term - Systemic effects 208 mg/m₃ (workers)

· Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:
- The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product. Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Printing date 03.11.2022

Version number 4

Revision: 03.11.2022

Trade name: Flüssigkeit für SHERADON

(Contd. of page 4)

· Eye/face protection



Tightly sealed goggles

· Body protection: Protective work clothing.

SECTION 9: Physical and chemic	al prope	erties
 9.1 Information on basic physical and c General Information 	hemical p	roperties
· Colour:		Colorless
· Odour:		characteristic
· Melting point/freezing point:		-48 °C
· Boiling point or initial boiling point and	boilina	
range		100.5 °C
· Flammability		Not applicable.
· Lower and upper explosion limit		
· Lower:		2.1 Vol %
· Upper:		12.5 Vol %
· Flash point:		10 °C
· Ignition temperature:		421 °C
· Decomposition temperature:		Not determined.
· pH		Not determined.
· Viscosity:		
· Kinematic viscosity at 20 °C		0.53 s (DIN 53211/4)
· Dynamic:		Not determined.
· Solubility		Not dotommod.
· water at 20 °C:		12.5 g/l
Partition coefficient n-octanol/water (log		1.38 log POW
Flüssigkeit für SHERADON	1,38 Log	
80-62-6 methyl methacrylate	1,38 Log	Pow
2082-81-7 tetramethylene dimethacrylate	3,1 Log P	
 Vapour pressure at 20 °C: 		36 hPa
 Density and/or relative density 		
· Density at 20 °C:		0.949 g/cm ³
· Relative density		Not determined.
· Vapour density		Not determined.
· 9.2 Other information		
· Appearance:		
· Form:		Fluid
 Important information on protection of 	health and	d
environment, and on safety.		
Auto-ignition temperature:		Product is not selfigniting.
 Explosive properties: 		Product is not explosive. However, formation of
		explosive air / vapour mixtures are possible.
· Solvent content:		
· VOC (EC):		90.00 %
· Solids content:		0.0 %
 Change in condition: 		
 Evaporation rate 		Not determined.
		(Contd. on page 6)

GB

Printing date 03.11.2022

Version number 4

Revision: 03.11.2022

Trade name: Flüssigkeit für SHERADON

		(Contd. of pag
· Information with regard to physical ha	azard	
classes		
· Explosives	Void.	
· Flammable gases	Void.	
Aerosols	Void.	
· Oxidising gases	Void.	
· Gases under pressure	Void.	
· Flammable liquids		
Highly flammable liquid and vapour.		
· Flammable solids	Void.	
 Self-reactive substances and mixtures 	Void.	
· Pyrophoric liquids	Void.	
· Pyrophoric solids	Void.	
 Self-heating substances and mixtures 	Void.	
 Substances and mixtures, which emit flamm 	able	
gases in contact with water	Void.	
· Oxidising liquids	Void.	
· Oxidising solids	Void.	
· Organic peroxides	Void.	
· Corrosive to metals	Void.	
· Desensitised explosives	Void.	

SECTION 10: Stability and reactivity

· 10.1 Reactivity Flammable, risk of ignition.

- 10.2 Chemical stability Stable under normal storage and handling conditions.
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid Keep away from heat.
- · 10.5 Incompatible materials No further relevant information available.
- · 10.6 Hazardous decomposition products No dangerous decomposition products known.

SECTION 11: Toxicological information

 \cdot 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity: Based on available data, the classification criteria are not met.

	ethyl met	
Oral	LD50	7,872 mg/kg (Rat)
Dermal	LD50	>5,000 mg/kg (Rabbit)
Inhalative	LC50/4 h	29.8 mg/l (Rat)
2082-81-7	tetrameth	nylene dimethacrylate
Oral	LD50	>10,000 mg/kg (Rat)
Dermal	LD50	>3,000 mg/kg (Rabbit)
Causes sk Serious e		

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB

Version number 4

Revision: 03.11.2022

Trade name: Flüssigkeit für SHERADON

rade name. Flussigken für Sheradon

(Contd. of page 6)

- Carcinogenicity Based on available data, the classification criteria are not met.
- \cdot Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure

Printing date 03.11.2022

May cause respiratory irritation.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

- Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

	•
 Aquatic tox 	cicity:
80-62-6 me	thyl methacrylate
LC50/96 h	>79 mg/l (Fish) (OECD 203)
EC50/48 h	69 mg/l (Daphnia (Daphnia magna)) (OECD 202)
NOEC, 21d	37 mg/l (Daphnia (Daphnia magna)) (OECD 202)
EC50/72 h	>110 mg/l (Algae) (OECD 201)
2082-81-7 t	etramethylene dimethacrylate
EC50/48h	7.51 mg/l (Daphnia (Daphnia magna)) (OECD 211)
LC50/96 h	32.5 mg/l (Fish)
NOEC	7.51 mg/l (Algae)
Other infor 12.3 Bioacc Distribution Based on th environmen 12.4 Mobili	tence and degradability No further relevant information available. mation: Biodegradable. cumulative potential coefficient (n-octanol / water) (log Pow): 1,38 re available data concerning eliminibility/degradation and bio-accumulation potential, longer-term tal damage is unlikely. ty in soil No adsorption in soil or sediment. s of PBT and vPvB assessment policable

- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation:

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Waste disposal according to official state regulations.

· Waste disposal key:

The waste disposal code as prescribed in the EuropeanWaste Catalogue (EWC) depends on the waste producer and can thus vary for a product. The waste disposal code should thus be obtained separately from the waste producer in each case.

Printing date 03.11.2022

Version number 4

Revision: 03.11.2022

Trade name: Flüssigkeit für SHERADON

(Contd. of page 7)

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number ADR, IMDG, IATA	UN1247
14.2 UN proper shipping name ADR	1247 METHYL METHACRYLATE MONOMER STABILIZED mixture
IMDG, IATA	METHYL METHACRYLATE MONOMER, STABILIZE mixture
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category Stowage Code	Warning: Flammable liquids. 33 F-E,S-D C SW1 Protected from sources of heat. SW2 Clear of living quarters.
14.7 Maritime transport in bulk according to IM instruments	O Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ): Excepted quantities (EQ):	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
Transport category: Tunnel restriction code:	2 D/E
IMDG Limited quantities (LQ): Excepted quantities (EQ):	1L Code: E2 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml

- GB

Printing date 03.11.2022

Version number 4

Revision: 03.11.2022

Trade name: Flüssigkeit für SHERADON

(Contd. of page 8)

· UN "Model Regulation":

UN 1247 METHYL METHACRYLATE MONOMER, STABILIZED MIXTURE, 3, II

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

- Employment restrictions concerning pregnant and lactating women must be observed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on the state of knowledge and experience pertaining on the date of issue. The information is not to be taken as a guarantee of product properties and do not constitute the basis for a contractual legal relationship. The details must not be changed or transferred to other products. Duplication in an unchanged state is permissible.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.

· Department issuing SDS: Department of product security.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

- $\label{eq:GHS:Globally} GHS: Globally \mbox{ Harmonised System of Classification and Labelling of Chemicals}$
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU)
- DNEL: Derived No-Effect Level (UK REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids . Category 2 Skin Irrit. 2: Skin corrosion/irritation . Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation . Category 2
- Skin Sens. 1: Skin sensitisation . Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) . Category 3
- \cdot * Data compared to the previous version altered.

GB