Printing date 04.03.2021 Version number 2 Revision: 04.03.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SHERAprint-tray clear
- · Article number: SD400140
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

- · Application of the substance / the mixture: 3D printed material.
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Hersteller:

Deltamed GmbH

Raiffeisenstr. 8a

D-61169 Friedberg

+49 (0) 6031 7283-0

info@deltamed.de

www.deltamed.de

Lieferant:

SHERA Werkstoff-Technologie GmbH & Co. KG

Espholstraße 53

D-49448 Lemförde

sdb@shera.de

+ 49 (0) 5443 9933-0

- · Further information obtainable from: Department of product security.
- · 1.4 Emergency telephone number:

Giftinformationszentrum-Nord: +49 (0) 551-19240

(Information in german or english)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- \cdot Classification according to Regulation (EC) No 1272/2008:

Skin Irrit. 2

H315 Causes skin irritation.

Skin Sens. 1

H317 May cause an allergic skin reaction.

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms:





GHS07

S07 GHS09

- · Signal word: Warning
- · Hazard-determining components of labelling:

dimethacrylate

Acrylic resin

2,2-bis(acryloyloxymethyl)butyl acrylate

Phosphine oxide

Hazard statements:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 04.03.2021 Version number 2 Revision: 04.03.2021

Trade name: SHERAprint-tray clear

· Precautionary statements:

P261 Avoid breathing dust / fume / gas / mist / vapours / spray.

P273 Avoid release to the environment.
P280 Wear protective gloves / eye protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P391 Collect spillage.

P501 Dispose of contents / container in accordance with local / regional / national / international

regulations.

2.3 Other hazards

In the presence of radical formers (e.g. peroxide), reducing substances and/or heavy metal ions, polymerisation is possible when heat develops.

- · Results of PBT and vPvB assessment:
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of acrylic resins and initiators.

· Dangerous components:		
	dimethacrylate Skin Sens. 1, H317; Aquatic Chronic 3, H412	<70%
	Acrylic resin Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Skin Sens. 1, H317	<40%
	Acrylic resin Aquatic Chronic 2, H411; Skin Sens. 1B, H317	<20%
CAS: 15625-89-5 EINECS: 239-701-3 Index number: 607-111-00-9	2,2-bis(acryloyloxymethyl)butyl acrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	1-<5%
CAS: 75980-60-8 EINECS: 278-355-8 Index number: 015-203-00-X Reg.nr.: 01-2119972295-29	Phosphine oxide Repr. 2, H361f; Aquatic Chronic 2, H411; Skin Sens. 1, H317	<1%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · General information: In case of troubles or persistent symptoms, consult an medical.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

After contact with skin, wash immediately with plenty of water and soap.

If skin irritation continues, consult a doctor.

Remove dirty clothing and wash before using again.

Immediately wash with water and soap and rinse thoroughly.

After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)

(Contd. of page 1)

Printing date 04.03.2021 Version number 2 Revision: 04.03.2021

Trade name: SHERAprint-tray clear

(Contd. of page 2)

\cdot 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents:

Use fire extinguishing methods suitable to surrounding conditions.

Carbon dioxide.

Fire-extinguishing powder.

Foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet.

5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Carbon monoxide (CO).

Carbon dioxide (CO□).

Pyrolysis products, toxic.

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Avoid contact with skin and eyes.

Do not breathe vapour or spray.

Use respiratory protective device against the effects of fumes / dust / aerosol.

Wear protective clothing.

- 6.2 Environmental precautions Do not allow to enter sewers / surface or ground water.
- \cdot 6.3 Methods and material for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Do not breathe vapours.

Store in cool, dry place in tightly closed receptacles.

Keep away from heat and direct sunlight.

Ensure good ventilation / exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Protect from direct sunlight.

In case of fire, cool endangered receptacles with water spray.

Keep ignition sources away - Do not smoke.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage
- \cdot Requirements to be met by storerooms and receptacles:

Store only in the original receptacle.

(Contd. on page 4)

Printing date 04.03.2021 Version number 2 Revision: 04.03.2021

Trade name: SHERAprint-tray clear

(Contd. of page 3)

Keep away from light.

Keep container tightly closed.

Might polymerize with high heat release.

Storage temperature between 4 and 25°C.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class:

TRGS 510: 10 (flammable liquids that are not assigned to any of the aforementioned LGK storage classes)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

15625-89-5 2,2-bis(acryloyloxymethyl)butyl acrylate

MAK (Germany) cf. Section.IV

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

Ensure good ventilation / exhaustion at the workplace.

Pregnant women should strictly avoid inhalation or skin contact.

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Hand protection

Protective gloves should be changed regularly, in particular after intensive contact with the product.



Protective gloves

The glove material has to be impermeable and resistant to the product. Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

· Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Safety glasses.
- · Body protection: Protective work clothing.

GB

Printing date 04.03.2021 Version number 2 Revision: 04.03.2021

Trade name: SHERAprint-tray clear

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Colour: Pink

Odour: characteristicMelting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

range Undetermined. • Flammability Not applicable.

Lower and upper explosion limit

Lower: Not determined.
Upper: Not determined.
Flash point: >150 °C

· **Auto-ignition temperature:** Product is not selfigniting.

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosity
 Dynamic at 20 °C:
 Not determined.
 500 - 1000 mPas

Solubility

• water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure:
 Not determined.
 Not determined.

· Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and environment, and on safety.

• Explosive properties: Product does not present an explosion hazard.

Solvent content:

· Solids content: Not determined.

· Change in condition:

• Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void. Flammable gases Void. · Aerosols Void. · Oxidising gases Void. Gases under pressure Void. · Flammable liquids Void. Flammable solids Void. · Self-reactive substances and mixtures Void.

Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Void.

Substances and mixtures, which emit flammable

gases in contact with water Void.

Oxidising liquids Void.
Oxidising solids Void.
Organic peroxides Void.

(Contd. on page 6)

Printing date 04.03.2021 Version number 2 Revision: 04.03.2021

Trade name: SHERAprint-tray clear

(Contd. of page 5)

Corrosive to metalsDesensitised explosivesVoid.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No decomposition if used according to specifications.
- 10.2 Chemical stability No decomposition if used according to specifications.
- · Thermal decomposition / conditions to be avoided: Keep away from heat. Protect from direct sunlight.
- 10.3 Possibility of hazardous reactions

Polymerization with heat release is possible in connection with radical forming agents (e.g. peroxides), reducing agents and/or heavy metal ions.

· 10.4 Conditions to avoid

Protect from exposure to light.

Only store in the original container at a temperature of between 4 and 25°C.

Can polymerise with severe heat development.

· 10.5 Incompatible materials

Oxidizing agents.

Reducing agents.

Acids.

Alkalis (alkalis).

Metal.

· 10.6 Hazardous decomposition products No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity: Based on available data, the classification criteria are not met.

Tions to Notify Based on available data, the sladelineation of the met.					
· LD/LC5	LD/LC50 values relevant for classification:				
dimetha	acrylat	е			
Oral	LD50	>2,000 mg/kg (Rat)			
Acrylic	Acrylic resin				
Oral	LD50	>2,000 mg/kg (Rat)			
Dermal	LD50	>2,000 mg/kg (Rat)			
75980-6	30-60-8 Phosphine oxide				
Oral	LD50	>5,000 mg/kg (Rat)			
Dermal	LD50	>2,000 mg/kg (Rat)			

Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 7)

Printing date 04.03.2021 Version number 2 Revision: 04.03.2021

Trade name: SHERAprint-tray clear

11.2 Information on other hazards

(Contd. of page 6)

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

Acrylic resin

LC50/96 h | 4.95 mg/l (Fish)

75980-60-8 Phosphine oxide

EC50/48 h | 3.53 mg/l (Daphnia (Daphnia magna))

EC10 1.56 my (Algae) EC50/72 h >2.01 mg/l (Algae) LC50/48 h 6.53 mg/l (Fish)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Remark: Toxic for fish.
- · Additional ecological information:
- · General notes:

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation:

Smaller quantities could be cured with light and can be disposed of as household waste. Larger quantities shall be disposed of as special waste in accordance with local regulations.

· Waste disposal key:

The waste disposal code as prescribed in the EuropeanWaste Catalogue (EWC) depends on the waste producer and can thus vary for a product. The waste disposal code should thus be obtained separately from the waste producer in each case.

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

GB

Printing date 04.03.2021 Version number 2 Revision: 04.03.2021

Trade name: SHERAprint-tray clear

(Contd. of page 7)

SECTION 14: Transport information	
14.1 UN number or ID number ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR	3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (Acrylic resin, Acrylic resin)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE LIQUID, N.O.S. (Acrylic resin, Acrylic resin), MARIN POLLUTANT ENVIRONMENTALLY HAZARDOUS SUBSTANCE
IATA	LIQUID, N.O.S. (Acrylic resin, Acrylic resin)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	9 Miscellaneous dangerous substances and articles.9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards: Marine pollutant: Special marking (ADR): Special marking (IATA):	Product contains environmentally hazardous substances Acrylic resin Symbol (fish and tree) Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user Hazard identification number (Kemler code):	Warning: Miscellaneous dangerous substances an articles. 90
EMS Number: Stowage Category	F-A,S-F A
14.7 Maritime transport in bulk according to II instruments	MO Not applicable.
Transport/Additional information:	
ADR Limited quantities (LQ): Excepted quantities (EQ):	5L Code: E1 Maximum net quantity per inner packaging: 30 ml
Transport category:	Maximum net quantity per outer packaging: 1000 ml
IMDG Limited quantities (LQ):	5L
Excepted quantities (EQ):	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (ACRYLIC RESIN ACRYLIC RESIN), 9, III

Printing date 04.03.2021 Version number 2 Revision: 04.03.2021

Trade name: SHERAprint-tray clear

(Contd. of page 8)

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category E2 Hazardous to the Aquatic Environment
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

• 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on the state of knowledge and experience pertaining on the date of issue. The information is not to be taken as a guarantee of product properties and do not constitute the basis for a contractual legal relationship. The details must not be changed or transferred to other products. Duplication in an unchanged state is permissible.

Revision number: 1.20

· Relevant phrases

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H361f Suspected of damaging fertility.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Department of product security.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 2: Reproductive toxicity - Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

· * Data compared to the previous version altered.