

Printing date 16.02.2022

Version number 1

Revision: 16.02.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: SHERAprint-model stone
- Article number: SD400400
- **1.2 Relevant identified uses of the substance or mixture and uses advised against:** No further relevant information available.
- · Application of the substance / the mixture: 3D printing material
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier: SHERA Werkstoff-Technologie GmbH & Co. KG Espohlstraße 53 D-49448 Lemförde GERMANY sdb@shera.de + 49 (0) 54 43 . 99 33 . 0
- · Further information obtainable from: Department of product security.
- · 1.4 Emergency telephone number:
- Giftinformationszentrum-Nord: +49 (0) 551-19240
- (Information in german or english)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008:

Skin Irrit. 2	H315 Causes skin irritation.
Eye Irrit. 2	H319 Causes serious eye irritation.
Skin Sens. 1	H317 May cause an allergic skin reaction.
Aquatic Chronic 2	H411 Toxic to aquatic life with long lasting effects.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008:

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms:



· Signal word: Warning

- · Hazard-determining components of labelling:
- Aliphatic Diacrylate
- Acryliertes Harz
- Phosphine oxide

phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

- · Hazard statements:
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H317 May cause an allergic skin reaction.
- H411 Toxic to aquatic life with long lasting effects.
- \cdot Precautionary statements:
- P261 Avoid breathing mist/vapours/spray.
- P273 Avoid release to the environment.
- P280 Wear protective gloves / protective clothing.
- P302+P352 IF ON SKIN: Wash with plenty of water.

(Contd. on page 2)



Revision: 16.02.2022

Printing date 16.02.2022

Version number 1

Trade name: SHERAprint-model stone

(Contd. of page 1)

- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P501 Dispose of contents / container in accordance with local / regional / national / international regulations.

· 2.3 Other hazards

- · Results of PBT and vPvB assessment:
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Acrylic/methacrylate resins with additives.

· Dangerous components:

	Aliphatic Diacrylate	25-90%
	Aquatic Chronic 2, H411; Skin Sens. 1B, H317	
	Acryliertes Harz	5-40%
	Aquatic Chronic 2, H411; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317	
CAS: 444649-70-1	Acrylate resin	5-40%
EC number: 814-233-8 Reg.nr.: 01-2120271347-53	Aquatic Chronic 2, H411	
CAS: 75980-60-8 EINECS: 278-355-8 Index number: 015-203-00-X Reg.nr.: 01-2119972295-29	Phosphine oxide	0.1-2.5%
	Repr. 2, H361f; Aquatic Chronic 2, H411; Skin Sens. 1, H317	
CAS: 162881-26-7	phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide	0.1-5%
ELINCS: 423-340-5 Index number: 015-189-00-5 Reg.nr.: 01-2119489401-38	Skin Sens. 1A, H317; Aquatic Chronic 4, H413	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact:
- In case of skin irritation, seek medical treatment.
- Remove dirty clothing and wash before using again.
- Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: Rinse out mouth and then drink plenty of water.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

(Contd. on page 3)



Revision: 16.02.2022

Printing date 16.02.2022

Version number 1

Trade name: SHERAprint-model stone

(Contd. of page 2)

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fire with alcohol resistant foam. Use fire extinguishing methods suitable to surrounding conditions.
5.2 Special hazards arising from the substance or mixture In case of fire, the following can be released: Carbon dioxide (CO₂). Carbon monoxide (CO). Pyrolysis products, toxic.
5.3 Advice for firefighters
Protective equipment: Wear self-contained respiratory protective device. Wear fully protective suit.
Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation. Use respiratory protective device against the effects of fumes / dust / aerosol. Wear protective clothing. Avoid contact with skin and eyes.
 6.2 Environmental precautions Inform respective authorities in case of seepage into water course or sewage system. Dilute with plenty of water. Do not allow to enter sewers / surface or ground water.
 6.3 Methods and material for containment and cleaning up Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.
 6.4 Reference to other sections See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

7.1 Precautions for safe handling
 Devices with local extraction are to be used for open handling.
 Ensure good ventilation / exhaustion at the workplace.

 Prevent formation of aerosols.
 Information about fire - and explosion protection: No specific

· Information about fire - and explosion protection: No special measures required.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and receptacles:
 Store only in the original receptacle.
 Keep container in a well-ventilated, cool and dry place.
 Store only in the tightly closed original container at room temperature.
 Keep away from light.
 Might polymerize with high heat release.
 Storage temperature between 4 and 28°C.

· Information about storage in one common storage facility: Not required.

(Contd. on page 4)

GB

SHERA[®] IWERKSTOFF ITECHNOLOGIE

Safety data sheet according to 1907/2006/EC, Article 31

Version number 1

Trade name: SHERAprint-model stone

Printing date 16.02.2022

(Contd. of page 3)

Revision: 16.02.2022

• Further information about storage conditions: Do not store in a protective gas environment, as oxygen (in the air) is required for stabilisation.

Keep container tightly sealed.

- · Storage class: No information available.
- 7.3 Specific end use(s) No further relevant information available.
- **SECTION 8: Exposure controls/personal protection**
- · 8.1 Control parameters
- · Ingredients with limit values that require monitoring at the workplace:
- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:
- Ensure good ventilation / exhaustion at the workplace.
- Pregnant women should strictly avoid inhalation or skin contact.
- The usual precautionary measures are to be adhered to when handling chemicals.
- Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product. Due to missing tests no recommendation to the glove material can be given for the product. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves:

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material:

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- Eye/face protection Goggles recommended during refilling
- · Body protection: Protective work clothing.

	ysical and chemical properties	
General Information		
Colour:	Grey	
Odour:	characteristic	



Printing date 16.02.2022

Version number 1

Revision: 16.02.2022

Trade name: SHERAprint-model stone

	(Contd. of pag
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling	
range	Undetermined.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	Not applicable.
· Auto-ignition temperature:	Product is not selfigniting.
· Decomposition temperature:	Not determined.
· pH	Not determined.
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic at 20 °C:	500-1,000 mPas
Solubility	
· water:	Insoluble.
• Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
· · ·	
• 9.2 Other information	
· Appearance:	
· Form:	Fluid
 Important information on protection of health and 	1
environment, and on safety.	
· Explosive properties:	Product does not present an explosion hazard.
· Solvent content:	
· VOC (EC):	0,00 %
· Solids content:	0.0 %
· Change in condition:	
· Evaporation rate	Not determined.
·Information with regard to physical hazard	ł
classes	
· Explosives	Void.
· Flammable gases	Void.
· Aerosols	Void.
· Oxidising gases	Void.
· Gases under pressure	Void.
· Flammable liquids	Void.
· Flammable solids	Void.
· Self-reactive substances and mixtures	Void.
· Pyrophoric liquids	Void.
	Void.
· Pyrophoric solids	
 Pyrophoric solids Self-heating substances and mixtures 	VOID
Self-heating substances and mixtures	Void.
 Self-heating substances and mixtures Substances and mixtures, which emit flammable 	
 Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water 	Void.
 Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids 	Void. Void.
 Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids 	Void. Void. Void.
 Self-heating substances and mixtures Substances and mixtures, which emit flammable 	Void. Void.



Printing date 16.02.2022

Version number 1

Revision: 16.02.2022

(Contd. of page 5)

Trade name: SHERAprint-model stone

· Desensitised explosives

Void.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No data available.
- · 10.2 Chemical stability No decomposition if used according to specifications.
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with acids, alkalis and oxidising agents.
- · 10.4 Conditions to avoid
- The product hardens under the influence of visible and UV light. Therefore, keep them in closed containers at 4 ° C -28 ° C with complete exclusion of light.
- · 10.5 Incompatible materials

Oxidizing agents. Reducing agents. Acids.

Alkalis (alkalis).

Metal.

10.6 Hazardous decomposition products

If the product is exposed to fire, it can release caustic acrylate vapours.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity: Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

-	ic Diacry	
Oral	LD50	>2,000 mg/kg (Rat)

Dermal LD50 >2,000 mg/kg (Rabbit)

Acryliertes Harz

Oral NOAEL >1,000 mg/kg (Rat)

LD50 >2,000 mg/kg (Rat)

Dermal LD50 >2,000 mg/kg (Rabbit)

75980-60-8 Phosphine oxide

Oral LD50 >5,000 mg/kg (Rat)

Dermal LD50 >2,000 mg/kg (Rat)

162881-26-7 phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide

Oral LD50 >2,000 mg/kg (Rat) (OECD 402)

• Skin corrosion/irritation Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

- · Respiratory or skin sensitisation
- May cause an allergic skin reaction.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

- **STOT-single exposure** Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. on page 7)

GB



Printing date 16.02.2022 Version number 1 Revision: 16.02.2022 Trade name: SHERAprint-model stone (Contd. of page 6) · 11.2 Information on other hazards · Endocrine disrupting properties None of the ingredients is listed. **SECTION 12: Ecological information** · 12.1 Toxicity · Aquatic toxicity: **Aliphatic Diacrylate** EC50/48h 2.36 mg/l (Daphnia (Daphnia magna)) (OECD 202) Acryliertes Harz EC50/48h >34 mg/l (Daphnia (Daphnia magna)) (OECD 202) 75980-60-8 Phosphine oxide EC50/48 h 3.53 mg/l (Daphnia (Daphnia magna)) EC10 1.56 my (Algae) EC50/72 h >2.01 mg/l (Algae) LC50/48 h 6.53 mg/l (Fish) 162881-26-7 phenyl bis(2,4,6-trimethylbenzoyl)-phosphine oxide LC50/96 h >0.09 mg/l (Fish) EC50/48 h >1.175 mg/l (Daphnia (Daphnia magna)) NOEC >0.008 mg/l (Daphnia (Daphnia magna)) · 12.2 Persistence and degradability No further relevant information available. · 12.3 Bioaccumulative potential No further relevant information available. · 12.4 Mobility in soil No further relevant information available. 12.5 Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. · 12.6 Endocrine disrupting properties The product does not contain substances with endocrine disrupting properties. · 12.7 Other adverse effects · Remark: Harmful to fish. · Additional ecological information: · General notes: Harmful to aquatic organisms. Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water. Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation:

Smaller quantities could be cured with light and can be disposed of as household waste. Larger quantities shall be disposed of as special waste in accordance with local regulations.

· Waste disposal key:

The waste disposal code as prescribed in the EuropeanWaste Catalogue (EWC) depends on the waste producer and can thus vary for a product. The waste disposal code should thus be obtained separately from the waste producer in each case.

(Contd. on page 8)

GB



Revision: 16.02.2022

Printing date 16.02.2022

Version number 1

Trade name: SHERAprint-model stone

(Contd. of page 7)

- · Uncleaned packaging:
- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

14.1 UN number or ID number	
ADR, IMDG, IATA	UN3082
14.2 UN proper shipping name ADR	3082 ENVIRONMENTALLY HAZARDOU SUBSTANCE, LIQUID, N.O.S. (Aliphatic Diacrylat Acryliertes Harz)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (Aliphatic Diacrylate, Acryliertes Harz MARINE POLLUTANT
ΙΑΤΑ	ENVIRONMENTALLY HAZARDOUS SUBSTANC LIQUID, N.O.S. (Aliphatic Diacrylate, Acryliertes Harz
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class Label	9 Miscellaneous dangerous substances and articles. 9
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	
Marine pollutant:	Symbol (fish and tree)
Special marking (ADR): Special marking (IATA):	Symbol (fish and tree) Symbol (fish and tree)
14.6 Special precautions for user	Warning: Miscellaneous dangerous substances ar
Hazard identification number (Kemler code):	articles. 90
EMS Number:	90 F-A,S-F
Stowage Category	A
14.7 Maritime transport in bulk according to IM	
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ):	5L
Excepted quantities (EQ):	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category:	3
Tunnel restriction code:	(-)



Printing date 16.02.2022

Version number 1

Revision: 16.02.2022

(Contd. of page 9)

Trade name: SHERAprint-model stone

	(Conta. of page 8)
·IMDG	
· Limited quantities (LQ):	5L
Excepted quantities (EQ):	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS
	SUBSTANCE, LIQUID, N.O.S. (ALIPHATIC
	DIACRYLATE, ACRYLIERTES HARZ), 9, III

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category E2 Hazardous to the Aquatic Environment
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements $200\ t$
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Information about limitation of use:
- Employment restrictions concerning juveniles must be observed.
- Employment restrictions concerning pregnant and lactating women must be observed.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on the state of knowledge and experience pertaining on the date of issue. The information is not to be taken as a guarantee of product properties and do not constitute the basis for a contractual legal relationship. The details must not be changed or transferred to other products. Duplication in an unchanged state is permissible.

· Relevant phrases

- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H361f Suspected of damaging fertility.
- H411 Toxic to aquatic life with long lasting effects.
- H413 May cause long lasting harmful effects to aquatic life.

· Department issuing SDS: Department of product security.

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Skin Irrit. 2: Skin corrosion/irritation . Category 2 Eye Irrit. 2: Serious eye damage/eye irritation . Category 2 Skin Sens. 1: Skin sensitisation . Category 1

Skin Sens. 1A: Skin sensitisation . Category 1A

(Contd. on page 10)



Printing date 16.02.2022

Version number 1

Revision: 16.02.2022

(Contd. of page 9)

Trade name: SHERAprint-model stone

Skin Sens. 1B: Skin sensitisation . Category 1B Repr. 2: Reproductive toxicity . Category 2 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard . Category 2 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard . Category 4

 \cdot * Data compared to the previous version altered.

GB